## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: M-Light

Supplier's address: Technik, Trinidadstr. 28 27356 Rotenburg

Model identifier: 81-2099

## Type of light source:

| Lighting technology used:     | LED            | Non-directional or directional: | NDLS |
|-------------------------------|----------------|---------------------------------|------|
| Light source cap-type         | constant       |                                 |      |
| (or other electric interface) | current 1050mA |                                 |      |
| Mains or non-mains:           | NMLS           | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No             | Envelope:                       | -    |
| High luminance light source:  | No             |                                 |      |
| Anti-glare shield:            | No             | Dimmable:                       | No   |

| Product parameters   |                                   |                           |   |              |  |  |  |
|--|-----------------------------------|---------------------------|---|--------------|--|--|--|
| Parameter  |                                   | Value                     | Parameter   | Value        |  |  |  |
| General product parameters:  |                                   |                           |   |              |  |  |  |
| Energy consum<br>mode (kWh/100<br>up to the neares                                     | 00 h), rounded                    | 40                        | Energy efficiency<br>class  | D            |  |  |  |
| Useful luminou<br>indicating if it re<br>in a sphere (36<br>cone (120º) or in<br>(90º) | efers to the flux 50°), in a wide | 6 631 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |  |  |
| On-mode p<br>expressed in W  | ower (P <sub>on</sub> ),          | 40,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |  |
| Networked stand<br>for CLS, expres<br>rounded to the s                                 | sed in W and                      | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |  |
| Outer  | Height                            | 3                         | Spectral power  | See image    |  |  |  |
| dimensions   | Width                             | 6                         | distribution in the   | in last page |  |  |  |
| without  | Depth                             | 1 465                     |   | Page 1 / 3   |  |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |             | range 250 nm to 800<br>nm, at full-load |       |
|--|-------------|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | -           | If yes, equivalent power (W)            | -     |
|  |             | Chromaticity<br>coordinates (x and y)   | 0,376 |
| Parameters for LED and OLED lig  | ht sources: |   |       |
| R9 colour rendering index value  | 5           | Survival factor                         | 0,90  |
| the lumen maintenance factor   | 0,95        |   |       |
| (a),   | I           |   |       |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

